

PRINCIPAL DIMENSIONS:

Length overall (Inc. pulpit) 50ft 3in (15.32m)

Length overall (ex pulpit) 49ft 2in (14.98m)

Beam 14ft 8in (4.47m)

Draft 3ft 8in (1.12m)

Fuel capacity 450 gallons (2045 liters)

Water capacity 125 gallons (568 liters)

ENGINES AND DRIVE:

TWIN CATERPILLAR C12 ACERT (2 X 715MHP)Caterpillar C12 Acert

OPTIONAL EQUIPMENTS FITTED:

Aft Cabin Fit Out

Hydraulic Passerelle With Remote Control

Additional 20m of 10mm Anchor Chain To Give A Total Of 60m

Continental 220v/240v Sockets

Foredeck Fresh Water Anchor/ Deck Wash System

Duplex Fuel Filter With Change Over \$%&!

Ice Maker (240v)

Washer/Dryer In Utility Space Below Galley

A 26" Lcd TV Is Fitted As Standard In The Lower Saloon

Standard Audio System

Upper Saloon & Cockpit-Bose Lifestyle 18 With Linked

Waterproof Speakers

Lower Saloon –Cd/Dvd

Master Stateroom – Jvc Cd/Radio

Cd/Radio For TV Aerial In Forward Cabin

Premium Audio System

Upper Saloon & Cockpit - Bose Lifestyle 48 Dvd Media System

Linked Waterproof Speakers And Separate Remote Control

Lower Saloon - Bose 3.2.1 Gs Dvd Media System Linked To Saloon

Lifestyle 48 System

Master Stateroom - Bose 3.2.1 Gs Dvd Media System Linked To Saloon

Lifestyle 48 System

26" Lcd TV In Master Stateroom Linked To Bose 3.2.1 Gs System
Raymarine C120w Radar /Chart plotter With Gps 48"Hd
Additional Raymarine C120w 12 At Upper Helm Position
Air-conditioning: System A: Suitable For Ambient Temperature To 35°C (E.G.
Florida/Eastern Mediterranean)
Condensing Unit 30,000 Btu Supplying 3 X 16,000 Btu
Outlets In Saloon (With Smx Control)
Condensing Unit 10,000 Btu Supplying 10,000 Btu
Outlets In Starboard Stateroom (With Smx Control)
And Deducted To Port Cabin
Condensing Unit 12,000 Btu Supplying 12,000 Btu
Outlet In Forward Stateroom (With Smx Control)
This Also Includes Outlets In Toilet Compartments.
Recommended Generator: 9.5kw
Mosquito Screens For Fitting To Portholes
Large Oval Mosquito Screens For Master Cabin
System 2: (Aft Cabin)
Toilet Discharging Into The Holding Tank But Also Having The Ability To
Discharge Directly Overboard Via A Y Valve Fitted In The Discharge- Lines.
The Holding Tank Has Electric Overboard Discharge As Well As Reserve
Manual And Dockside Discharge Agreement
Foredeck Sunbed Cushions – Movida
Cockpit Seating's In Movida
Bimini Top – White Pvc/Polyester
Fill Craft With Fuel
Ipod Docking Station Price Per Each
Onan 11 Kw /50 Hz Generator In Place Of Standard Onan 7kw